


TEK400MDx Series

300-400 Watt U-Frame Switching Power Supply
Dual Outputs ranging from 3.3~24 VDC



Product Features:

- Universal AC input with Power Factor Correction
- Safety Approved for Medical Applications
- Small Size of:
 - only 8.00 x 5.00 x 1.60" (U-Frame)
 - only 9.00 x 5.00 x 1.60" (End-Mount Fan Package)
- Full Featured Status & Control Signals
- 50~100% Voltage Margin Range
- Auxiliary Fan Output Function
- EN61000-3-2 / IEC100-3-2 Compliant
- Worldwide Safety Approvals
- EN55022 & FCC Class B Emissions
- CE Mark



INPUT SPECIFICATIONS:

VOLTAGE	Universal VAC In39put (90-264 VAC)
FREQUENCY	47-63Hz
INRUSH	35 @ 230VAC (Max Cold Start)
CURRENT	6.35A @ 90 VAC (Max Continuous)
PROTECTION	Dual 8A Fuse / 250 VAC
LEAKAGE	<150uA Max @ 264 VAC
HOLD-UP	20ms Minimum (80% Load)
HARMONICS	EN61000-3-2 Class D Compliant

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE	0 ~ +70°C (Derate 2.5% per °C above 50°C), Option "I" = -40~+75°C
STORAGE TEMPERATURE	-40 ~ +85°C
COOLING	18cfm Airflow for Full Load
HUMIDITY	5-95% (non-condensing)
VIBRATION	10-55Hz, 2G, 3Min Period, / 60 min each (3 axes)
SHOCK	20G Peak Acceleration
RELIABILITY	>100k Hrs (according to MIL-HBK-217F) at 30°C

OUTPUT SPECIFICATIONS:

ADJUSTMENT RANGE	±5 % (Minimum)
MINIMUM LOAD	None
LINE REGULATION	±1% Max over entire input range
LOAD REGULATION	±1% maximum
RIPPLE	±1% or 50mV pk-k max, whichever is greater (20MHz)
SETPOINT ACCURACY	±1%
OVER CURRENT	110~140% (Auto-Recovery)
OVER VOLTAGE PROTECTION	Latches >130% of Vnom

EMISSIONS:

EMISSIONS	EN55011 Level B (Conducted) / FCC Level B
ELECTROSTATIC DISCHARGE	EN61000-4-2, 4kV Contact / 8kV Air
RADIED SUSCEPTIBILITY	EN61000-4-3, 26-1000MHz, 10V/M, 80%AM
EFT / BURSTS	EN61000-4-4, 2kV
SURGES	EN61000-4-5, 2kV Earth, 1kV Line-Line
CONDUCTED IMMUNITY	EN61000-4-6, 0.15-800MHz, 10V 80%
VOLTAGE DIPS	EN61000-4-10, 95% Dip & 10ms, 30% Dip & 500ms
VOLTAGE INTERRUPTIONS	EN61000-4-11, 95% reduction, 5ms
FLUCTUATIONS & FLICKER	EN61000-3-3

STATUS & CONTROL SPECIFICATIONS:

REMOTE SENSE	Compensates for up to 250mV Drop
REMOTE ON/OFF	Low Signal turn off the supply
AC FAIL	Low = AC input <80VAC
REMOTE MARGIN	0.4~5.0 Signal for 50~100 Voltage Adjustment
CURRENT SHARE (OPTION)	±10% Accuracy (4 units maximum)
CURRENT MONITOR	0.5~3.0V Signal for 0~100% Load

SAFETY STANDARDS:

UL /CUL	60601-1
CSA	22.2 No. 60601-1
TUV	EN60601-1
CE MARK	Low Voltage Directive




lhvpower.com

TEK400MDx Series

300-400 Watt U-Frame Switching Power Supply
Dual Outputs ranging from 3.3~24 VDC

PART #	OUTPUTS				NOTE
	V1 / A1	V2 / A2	V3 / A3	V4 / A4	
TEK400MDx-0312	+3.3 40.0A	+12V 25.00A			300 Watts Max Continuous Output Power
TEK400MDx-0324	+3.3V 40.00A	+24V 12.50A			300 Watts Max Continuous Output Power
TEK400MDx-0512	+5.0V 40.00A	+12V 25.00A			300 Watts Max Continuous Output Power
TEK400MDx-0524	+5.0V 40.00A	+24V 12.50A			300 Watts Max Continuous Output Power
TEK400MDx-1224	+12V 25.00A	+24V 12.50A			400 Watts Max Continuous Output Power

- Replace "x" with the options below to designate preferred mechanical package: U = U-Frame Package E = Enclosed Type +
- For Enclosed Models only, Add Suffix to designate Input Connector: "A" = Terminal Block | "B" = IEC-320 with Switch
- Default Connections are Terminal Block (no suffix required):
 - Add the Suffix "C" to designate Molex Output Connector for Enclosed Models
 - Add the Suffix "T" to designate Terminal Block Input / Molex Output Connector (for U-Frame Models only)
 - Add the Suffix "H" to designate Molex Input & Output Connectors (for U-Frame Models)
- Output Connector (CN2): Mating Molex 16 pins (09-91-1600), or Howder (HD-121-6P) M3.5, 8 pins terminal block, 9.5MM Center.
- Logic signal connectors (CN3): Mating JST XHP-5 or equivalent (CHYAO SHIUNN JS-2001-05). Mating Pins: JST SXH-002T-P0.6 FOR AWG 30 to 26.
- Mounting Inserts: 6-32, M4 4 Places individually with maximum penetration 0.15" on bottom side and 0.25" on both side.



lhvpower.com